




FINfloor VINYL PRO

CLASS OF USE ACCORDING EN 10874	23 / 33 / 42		
			

CHARACTERISTIC	FINfloor VINYL PRO	Test method
Total thickness	4,5 mm	EN ISO 24346
Wear layer	0,55 mm	EN ISO 24340
Surface treatment	PUR layer	
Total weight (g/m2)	7.681	EN ISO 23997
Plancks	191 x 1316 mm	EN ISO 24342
Box planks	1,76 m2/box	
Inflammability	Bfl s1	EN 13501
Scratch resistance	Class T	EN 660-2
Squareness and straightness	≤ 0,35 mm	EN ISO 24342
Slip resistance	DS	EN 13893
Slip restraint	R10	DIN 51130
Residual indentation	≤ 0,10 mm	EN ISO 24343
Furniture leg resistance	No cracks , no dammagess	EN ISO 16581
Curling	≤ 2mm	EN ISO 23999
Electrical resistance	≤ 10 ⁹	EN ISO 10965
Dimensional stability	Nominal ≤ 0,25 % Measured ≤ 0,05 %	EN ISO 23999
Heat insulation	0,25 W/m.K	EN 12524
Thermal resistance	0,0159 m2.K / W	EN ISO 12664
Electrostatic performance	≤ 2 kV	EN 1815
Formaldehyde group	E1	EN 717-1
Acoustic insulation	4 dB	EN 140-8
Castor chair resistance	No damage,no delamination	EN 425
Stain resistance	Very good	EN ISO 26987
Light fastness	≥ 6	ISO 105-B02
Underfloor heating	Suitable , max. 27°C	EN 12524
Warranty	20 residential / 10 commercial	